

Turbo-charge your jets with a Santanna Blower!

Special Features:

- Foam packed, durable polypropylene casing allows noise-free operation
- Side or bottom outlet for *easy outdoor installation*
- Heat-free open-air system eliminates backpressure build-up
- Internal check valve resists water damage
- Thermal protection equipped with automatic reset
- Body is made with Hi-Temp PVC
- Side/bottom outlet is perfect for any outdoor installation
- Slip plug included
- UL and CSA certified
- Santanna Air Blowers offer full one-year warranty against water damage
- Wall-mount bracket is included



Santanna

A I R B L O W E R B Y W A T E R W A Y

Part Number	HP	Volts	Amps	Diameter	Orifice (CFM)	Air Flow P.S.I.
750-1011-280	1.0	110	7.0	2"	115	2.1
750-1022-280	1.0	220/240	3.5	2"	113	3.8
750-1511-280	1.5	110	8.0	2"	120	4.2
750-1522-280	1.5	220/240	4.0	2"	108	2.1
750-2011-280	2.0	110	9.0	2"	128	3.8
750-2022-280	2.0	220	6.0	2"	119	4.2

For Residential Use Only

Available



600-8140 Air Check Valve (U.L. Listed SA8537)
 1½" Slip, 2" Spigot x 1½" S - 2" Spigot, ¼ lb. Spring
 (sold separately)

Number of Jets Blower Size

- 4 - 7** 1 HP
- 8 - 13** 1½ HP
- 14 +** 2 HP

When using a blower to turbo charge jets, care must be taken in sizing and installation. It is important not to oversize the blower. The chart is a general guideline.

Waterway™

2200 East Sturgis Road, Oxnard, California 93030 • Ph. 805-981-0262 • Fax 805-981-9403
 waterway@waterwayplastics.com • www.waterwayplastics.com

Be Sure it's
Genuine

