

NEW! ULTRA-QUIET BLOWERS



Stealth II Blower



FEATURES

- High performance motor runs cooler and quieter
- High impact resistant construction
- Has been tested, certified and listed by UL to requirements of both UL and CSA standards

FEATURES

- Side or bottom mount
- Heat-free due to open air system that eliminates back pressure build-up
- Internal check valve resists water damage
- Mounting body is Hi-Temp material
- Protected for the locked motor condition
- Side/Bottom outlet is perfect for any outdoor installation; slip plug is included for the outlet not in use
- Has been tested, certified and listed by UL to requirements of both UL and CSA standards
- Santanna II Air Blowers for residential use are backed by a full one-year, no water damage, warranty
- Bracket on case for easy mounting
- High impact strength construction
- Indoor/outdoor use



Stealth Air Blowers

| Part No. | Description | HP | Volts | Amps |
|--------------|----------------------|-----|-------|------|
| 700-1011-000 | 1 1/2" S / 2" Spigot | 1.0 | 110 | 6.7 |
| 700-1511-000 | 1 1/2" S / 2" Spigot | 1.5 | 110 | 7.6 |
| 700-1022-000 | 1 1/2" S / 2" Spigot | 1.0 | 220 | 4.0 |
| 700-1522-000 | 1 1/2" S / 2" Spigot | 1.5 | 220 | 4.2 |
| 700-2011-000 | 1 1/2" S / 2" Spigot | 2.0 | 110 | 8.8 |
| 700-2022-000 | 1 1/2" S / 2" Spigot | 2.0 | 220 | 5.8 |

INCLUDED

600-8140 & 600-8160 Air Check Valve
(U.L. Listed SA8537)

1 1/2" Slip, 2" Spigot x 1 1/2" S -
2" Spigot, 1/4 lb. Spring

| Number of Jets | Blower Size |
|----------------|-------------|
| 4 - 7 | 1 HP |
| 8 - 13 | 1 1/2 HP |
| 14 + | 2 HP |



When using a blower to turbo charge jets, care must be taken in sizing and installation. It is important not to oversize the blower.

Santanna Air Blowers

| Part No. | HP | Volts | Amps | Orifice Dia. | Air Flow (CFM) | PSI |
|--------------|-----|-------|------|--------------|----------------|-----|
| 750-1011-280 | 1.0 | 110 | 7.0 | 2" | 115 | 2.1 |
| 750-1022-280 | 1.0 | 220 | 3.5 | 2" | 113 | 3.8 |
| 750-1511-280 | 1.5 | 110 | 8.0 | 2" | 120 | 4.2 |
| 750-1522-280 | 1.5 | 220 | 4.0 | 2" | 108 | 2.1 |
| 750-2011-280 | 2.0 | 110 | 9.0 | 2" | 128 | 3.8 |
| 750-2022-280 | 2.0 | 220 | 6.0 | 2" | 119 | 4.2 |



2200 East Sturgis Road, Oxnard CA 93030 • Ph. 805.981.0262 • Fax 805.981.9403
waterway@waterwayplastics.com • www.waterwayplastics.com

Made in
the USA



©2011 Waterway Plastics