



ProClean™

Single Cartridge Filter

Designed for in-ground or above ground installations, the Pro-Clean Cartridge Filter has a raised inlet for easy plumbing from the pump. Molded of ABS thermoplastic material for exceptional performance and long life, the Pro-Clean Cartridge Filter will provide years of dependable service.



Features:

- 2" FPT inlet and outlet for more flow
- Raised inlet for easier plumbing from pump
- The Pro-Clean Filter's large air relief valve makes service faster and easier
- Lid lock-ring handle makes removing the lid easy and safe
- Internal designed for more dirt holding capacity and longer cleaning cycles
- Drain plug is 3/4". Can install a standard 3/4" hose valve for draining
- "Start-Service" dial on stainless steel pressure gauge
- Molded ABS thermoplastic takes up very little room on any equipment pad

PROCLEAN CARTRIDGE FILTERS

Part No.	Description	Flow Rate	Pool Turnover 6 hours	Pool Turnover 8 hours
PCCF-075	75 sq. ft.	75 GPM	27,000	36,000
PCCF-100	100 sq. ft.	100 GPM	36,000	48,000
PCCF-125	125 sq. ft.	125 GPM	45,000	60,000
PCCF-150	150 sq. ft.	150 GPM	54,000	72,000
PCCF-175*	175 sq. ft.	150 GPM	54,000	72,000
PCCF-200*	200 sq. ft.	150 GPM	54,000	72,000

PRO-CLEAN D.E. CARTRIDGE FILTERS

The cleaning results of a D.E. with the convenience of a cartridge.

Part No.	Description
PCDE-30	30 sq. ft. D.E. Cartridge Filter
PCDE-40	40 sq. ft. D.E. Cartridge Filter

2200 East Sturgis Road, Oxnard, California 93030 • Ph. 805-981-0262 • Fax 805-981-9403
 waterway@waterwayplastics.com • www.waterwayplastics.com

