

ULTRA-QUIET BLOWERS!

Santanna II

Stealth II Blower



FEATURES

- High performance motor runs cooler & quieter
- High impact resistant construction
- Has been tested, certified and listed by UL to requirements of both UL & CSA standards

Stealth Air Blowers

Part No.	Description	HP	Volts	Amps
700-3011-000	1 1/2" S / 2" Spigot	1.0	110	6.7
700-3151-000	1 1/2" S / 2" Spigot	1.5	110	7.6
700-3102-000	1 1/2" S / 2" Spigot	1.0	220	4.0
700-3152-000	1 1/2" S / 2" Spigot	1.5	220	4.2
700-3201-000	1 1/2" S / 2" Spigot	2.0	110	8.8
700-3202-000	1 1/2" S / 2" Spigot	2.0	220	5.8

FEATURES

- Side or bottom mount
- Heat-free due to open air system that eliminates back pressure build-up
- Internal check valve resists water damage
- Mounting body is Hi-Temp material
- Side/Bottom outlet is perfect for any outdoor installation; slip plug is included for the outlet not in use
- Protected for the locked motor condition
- Has been tested, certified and listed by UL to requirements of both UL and CSA standards
- Santanna II Air Blowers for residential use are backed by a full one-year, no water damage, warranty
- Bracket on case for easy mounting
- High impact strength construction
- Indoor/outdoor use



Air Check Valves

600-8140 (included) & 600-8160 (U.L. Listed SA8537)

1 1/2" Slip, 2" Spigot x 1 1/2" S - 2" Spigot, 1/4 lb. Spring

Number of Jets	Blower Size
4 - 7	1 HP
8 - 13	1 1/2 HP
14 +	2 HP



When using a blower to turbo charge jets, care must be taken in sizing and installation. It is important not to oversize the blower.

Santanna Air Blowers

Part No.	HP	Volts	Amps	Orifice Dia.	Air Flow (CFM)	PSI
750-3101-280	1.0	110	7.0	2"	115	2.1
750-3102-280	1.0	220	3.5	2"	113	3.8
750-3151-280	1.5	110	8.0	2"	120	4.2
750-3152-280	1.5	220	4.0	2"	108	2.1
750-3201-280	2.0	110	9.0	2"	128	3.8
750-3202-280	2.0	220	6.0	2"	119	4.2



2200 East Sturgis Road, Oxnard, CA 93030 • Phone 805.981.0262 • Fax 805.981.9403
waterway@waterwayplastics.com • www.waterwayplastics.com



Designed,
Engineered &
Manufactured
in the USA.